

## Cable drum trailers LTV-R, SR, XR series ®

Registered European Model in 27 countries EU, nr. 000724323



Very soundly constructed drum carriers with superb looks. Available in various colours and load carrying capacities. Guaranteed long lived and underlining your image of progressive company.

Page 2: Unique product features

Page 3: Technical details and colours **LTV-R**

Page 4: Technical details and colours **LTV-SR, LTV-XR**

Venrooy Cable Equipment  
Simon Homburgstraat 12  
5431 NN Cuijk  
The Netherlands  
**T** +31 (0)485 33 60 60 (Kepser)  
**F** +31 (0)485 33 60 20  
**E** info@venrooy.nl  
**W** www.venrooy.nl

## Cable drum trailers LTV-R, SR, XR series ®

### Unique product features :




- An upside opening rear bridge (easier drum insertion)



- Sophisticated quicklocks of axle-insertionblock (faster and easier, no loose rattling parts anymore)



- Smart quicklocks for axle (faster and easier)



- Side-bars front/rear (road safety, protection mudguards, easy & safe to reach high for Operator)



- Compact, strongly improved springsystem



- Key operated built-in cilinder in frame for document storage (locked, safe storage)



- Drawbar lock (theft prevention)

Venrooy Cable Equipment  
Simon Homburgstraat 12  
5431 NN Cuijk  
The Netherlands  
**T** +31 (0)485 33 60 60 (Kepsers)  
**F** +31 (0)485 33 60 20  
**E** info@venrooy.nl  
**W** www.venrooy.nl

## Technical details LTV-R series ®

	<b>200R</b>	<b>250R</b>	<b>300R</b>	<b>350R</b>
Load carrying cap. kg	1.400	1.840	2.090	2.710
Mass empty kg	600	660	710	790
Mass maximum kg	2.000	2.500	2.800	3.500
Loading width	1,37 m	1,37 m	1,37 m	1,47 m
Drum Ø minimum	1,10 m	1,10 m	1,10 m	1,20 m
Drum Ø maximum	2,30 m	2,30 m	2,80 m	2,40 m
Spring system	independent	independent	independent	independent
Lifting system	hydraulic	hydraulic	hydraulic	hydraulic
Brake system	overrun	overrun	overrun	overrun
Coupling	ball	ball	ball	ball
Length carrier	3,70 m	3,70 m	4,25 m	4,04 m
Outside width carrier	2,23 m	2,23 m	2,23 m	2,34 m
Tyres	215/75R17,5	215/75R17,5	215/75R17,5	235/75R17,5
CE marking	yes	yes	yes	yes



## Standard colour combinations

	<u>Upper frame</u>	<u>Lower frame</u>	<u>Axle</u>
1.	Anthracite grey (standard)	Anthracite/silvergrey	Red
2.	In your house colour	Anthracite/silvergrey	Red

### Technical details LTV-SR series, LTV-XR series ®

	<b>S250R</b>	<b>S350R</b>		<b>X350R</b>	
	<b>single</b>	<b>single</b>	<b>tandem</b>	<b>single</b>	<b>tandem</b>
Load carrying cap. kg	1.765	2.765		2.640	
Mass empty kg	735	735		860	
Mass maximum kg	2.500	3.500		3.500	
Loading width	1,77 m	1,75 m	1,79 m	1,75 m	1,79 m
Drum Ø minimum	1,80 m	1,80 m	1,70 m	2,16 m	2,16 m
Drum Ø maximum	2,80 m	2,80 m		3,80 m	
Spring system	independent	independent		independent	
Lifting system	hydraulic	hydraulic		hydraulic	
Brake system	overrun	overrun		overrun	
Coupling	ball	ball		ball	
Length carrier	4,25 m	4,39 m	4,62 m	5,30 m	5,53 m
Outside width carrier	2,55 m	2,55 m		2,55 m	
Tyres	215/75 R17,5	235/75 R17,5	195x R14c	235/75 R17,5	195x R14c
CE marking	yes	yes		yes	



### Standard colour combinations

	<u>Upper frame</u>	<u>Lower frame</u>	<u>Axle</u>
1.	Anthracite grey (standard)	Anthracite/silvergrey	Red
2.	In your house colour	Anthracite/silvergrey	Red

Venrooy Cable Equipment  
 Simon Homburgstraat 12  
 5431 NN Cuijk  
 The Netherlands  
**T** +31 (0)485 33 60 60 (Kepser)  
**F** +31 (0)485 33 60 20  
**E** info@venrooy.nl  
**W** www.venrooy.nl